Heat Shrinkable End Cap (SHEC Series)

PRODUCT OVERVIEW:

Material: Cross-linked Polyolefin
- Spiral Adhesive Liner
- Chemical and Solvent Resistance
- Shrink Ratio: Not Less Than 2:1
- Color: Black
- Operating Temperature: From -55°C to 105°C
- Shrink Temperature: 125 °C
- Applicable for lead cables and PE Jacketed cables
- Not applicable to gas-filled air- tight cable

Application:
- For cable end and cable termination sealing of electrical cable, signal cable and other industrial cabling pipeline
- For energy supply infrastructure, chemical factories, oil refineries, metallurgy, harbor or other locations where safety and reliability of energy supplies are vital for daily operations



Part Number	As Supplied (mm)		After Recovered (mm)		
	D	A	D	L	W
SHEC-013/04	13	15	4	40	2.5
SHEC-015/05	15	18	5	45	2.5
SHEC-019/06	19	25	6	55	2.8
SHEC-025/08	25	30	8	68	2.8
SHEC-035/12	35	35	12	83	3.3
SHEC-040/15	40	35	15	90	3.3
SHEC-055/25	55	50	25	103	3.3
SHEC-063/24	63	70	24	140	3.5
SHEC-075/35	75	55	35	120	4.0
SHEC-100/50	100	70	50	140	3.5
SHEC-124/60	125	70	57	150	3.8
SHEC-148/57	148	70	57	150	4.1
SHEC-160/57	160	70	57	150	4.5

Remark: Suffix "A" means end cap with Air Valve.

Synerper Group Limited (A member of Synerper Corp Limited)
Room 704, 7/F., Crown Industrial Building, 106 How Ming Street, Kwun Tong, Kowloon, Hong Kong
TEL: +852 3590 9060 FAX: +852 3590 9061 email: synerper@synerper.com www.synerper.com