Synerper Wiring Duct (SWD Series)

PRODUCT OVERVIEW:

Material:
SWD-L: Polycarbonate(PC) +
Acrylonitrile Butadiene Styrene(ABS)
SWD-P: PVC
Colour: Light Grey
Working Temperature: -25˚C to +90˚C
Product Features:
-Enironmental Conservation, RoHS and REACH
-Flame Retardant, EN 45545
-Halogen Free, EN 45545
-Low Smoke Emission, EN 45545
-Shock Resistant, IEC 61373-2010
-Perfectly work with Wire Retainer and Cover

Low Smoke Halogen Free Wiring Duct

Part Number	Height (mm)	Width (mm)	Meter (M) Per Carton
SWD-L-3535	35	35	100
SWD-L-4025	40	25	100
SWD-L-4040		40	100
SWD-L-4060		60	64
SWD-L-4080		80	48
SWD-L-5035	50	35	100
SWD-L-5050		50	80
SWD-L-5080		80	48
SWD-L-6025	60	25	80
SWD-L-6040		40	64
SWD-L-6060		60	48
SWD-L-6080		80	36
SWD-L-8035	80	35	60
SWD-L-8040		40	48
SWD-L-8050		50	48
SWD-L-8060		60	36
SWD-L-8080		80	36
SWD-L-80100		100	24
SWD-L-10040	100	40	48
SWD-L-10050		50	48
SWD-L-10060		60	36
SWD-L-10075		75	24
SWD-L-100100		100	24

PVC Wiring Duct

Part Number	Height (mm)	Width (mm)	Meter (M) Per Carton
SWD-P-2525	25	25	100
SWD-P-3020	30	20	100
SWD-P-3025		25	100
SWD-P-3035		35	100
SWD-P-3535	35	35	100
SWD-P-4025	40	25	100
SWD-P-4040		40	100
SWD-P-4060		60	64
SWD-P-4080		80	48
SWD-P-4533	45	33	100
SWD-P-4545		45	80
SWD-P-5025	50	25	100
SWD-P-5035		35	100
SWD-P-5045		45	80
SWD-P-5050		50	80
SWD-P-5060		60	48
SWD-P-5080		80	48
SWD-P-6025	60	25	80
SWD-P-6040		40	64
SWD-P-6060		60	48
SWD-P-6080		80	36
SWD-P-6533	65	33	80
SWD-P-6545		45	80
SWD-P-6565		65	48
SWD-P-8025	80	25	60
SWD-P-8035		35	60
SWD-P-8040		40	48
SWD-P-8045		45	48
SWD-P-8050		50	48
SWD-P-8060		60	36
SWD-P-8080		80	36
SWD-P-80100		100	24
SWD-P-80120		120	24

Synerper Group Limited (A member of Synerper Corp Limited)
Room 704, 7/F., Crown Industrial Building, 106 How Ming Street, Kwun Tong, Kowloon, Hong Kong
TEL: +852 3590 9060 FAX: +852 3590 9061 email: synerper@synerper.com www.synerper.com